

MAINTENANCE SCHEDULE

The following items require some mechanical knowledge. Certain items (particularly those marked * and ** may require more technical information and tools. Consult your authorized Honda Dealer.

Perform the Pre-ride Inspection (page 39) at each scheduled maintenance period.

I: INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C: CLEAN R: REPLACE A: ADJUST L: LUBRICATE

ITEM	FREQUENCY	WHICHEVER →		ODOMETER READING [NOTE(1)]								Refer to
		COMES FIRST ↓	x1,000mi	0.6	4	8	12	16	20	24		
			NOTE	x1,000km	1	6.4	12.8	19.2	25.6	32.0	38.4	
* FUEL LINE						I		I		I		
* THROTTLE OPERATION						I		I		I		
* CARBURETOR CHOKE						I		I		I		
AIR CLEANER	NOTE (2)						R			R		
SPARK PLUG						R	R	R	R	R	R	Page 63
* VALVE CLEARANCE					I			I				
ENGINE OIL					R		R		R		R	Pages 59–62
ENGINE OIL FILTER					R		R		R		R	Pages 60–61
* CARBURETOR SYNCHRONIZATION						I	I	I	I	I	I	
* CARBURETOR IDLE SPEED					I	I	I	I	I	I	I	Page 65
RADIATOR COOLANT	NOTE (3)					I	I	I	I	R		Pages 23–24
* COOLING SYSTEM						I		I		I		
* SECONDARY AIR SUPPLY SYSTEM	NOTE (4)					I		I		I		
* EVAPORATIVE EMISSION CONTROL SYSTEM	NOTE (4)						I			I		

ITEM	FREQUENCY	WHICHEVER →		ODOMETER READING [NOTE(1)]								Refer to
		COMES FIRST ↓	x1,000mi	0.6	4	8	12	16	20	24		
			NOTE	x1,000km	1	6.4	12.8	19.2	25.6	32.0	38.4	
DRIVE CHAIN												
BRAKE FLUID												
BRAKE PAD WEAR	NOTE (3)					I	I	R	I	I	R	Pages 17–19
BRAKE SYSTEM						I		I		I		Page 20
* BRAKE LIGHT SWITCH												Pages 17–20
* HEADLIGHT AIM												
CLUTCH SYSTEM					I	I	I	I	I	I	I	Pages 21–22
SIDE STAND												
* SUSPENSION												Page 76
* NUTS, BOLTS, FASTENERS												
** WHEELS/TIRES												
** STEERING HEAD BEARINGS												

* SHOULD BE SERVICED BY AN AUTHORIZED HONDA DEALER UNLESS THE OWNER HAS PROPER TOOLS AND SERVICE DATA AND IS MECHANICALLY QUALIFIED. REFER TO THE OFFICIAL HONDA SERVICE MANUAL.

** IN THE INTEREST OF SAFETY, WE RECOMMEND THESE ITEMS BE SERVICED ONLY BY AN AUTHORIZED HONDA DEALER.

NOTES: (1) At higher odometer readings, repeat at the frequency interval established here.

(2) Service more frequently when riding in unusually wet or dusty areas.

(3) Replace every 2 years, or at indicated odometer interval, whichever comes first. Replacement requires mechanical skill.

(4) California type only.